

Passbook Printer

LPB 10



Key Applications

- Passbook updation
- Job card printing
- Cheque printing
- DD printing
- Single sheet printing

Features:

- One of the smallest and quietest models in its product class
- Superior printing speeds
- Process all bank forms
- Magnetic-stripe reading and writing
- Dual serial, dual USB, LAN interface available
- Ultra fast alignment

Specifications*:

Printer Type	: 24 pin dot matrix
Print Technology	: 24-pin dot matrix, Lifespan:> 400 million dots/needle
Print Speed (ASCII, @10 cpi)	: 660 cps (VHSD), 570 cps (HSD), 400 cps (Draft), 200 cps (NLQ), 135 cps (LQ)
Fonts	: OCR A-B, Roman, Sans Serif, Italic, Courier
Character Pitch	: 10,12,15,16.6,17.1,18,20 cpi
Line Length	: Max. 238.8 mm/94 columns at 10 cpi
Line Spacing	: 1/5", 1/6", n/216", n/240"
Documents Handling	: Feed width: 245 mm Horizontal feeding Auto alignment Automatic document thickness monitoring
Number of Copies	: 1 original + 6 copies
Emulations	: LQ, Olivetti PR2, PR2 plus, OKI, IBM PP II, X24 Optional: IBM4722/9068, IBMPP&X24, WINCOR4915, EPSON LQ2550, UNISYS EFP
Ribbon Cartridge	: 10Mn Characters,
Interface (standard)	: Serial RS232 + IEEE 1284 Parallel + USB2.0
Interface (optional)	: LAN, RS232 dual serial, dual USB2.0
Noise Level	: <52 dBA (ISO7779)
Power Consumption	: 2.5W (sleeping mode), 85W (Printing) Comply with Energy Star 2.0 standards
Voltage	: 220V/50Hz or 110V/60Hz
Dimensions, Weight	: 384 (W) x 280 (D) x 204 (H) mm, 10.5Kg.
MICR Option	: CMC7, E13B Speed: CMC7> 30cps, E13B>18cps
MSR Option	: Support DIN/ISO, ANSI, IBM3604 Compatible with IBM4746, ISO7811, HT-2751-C1Z, ISO8484
Print Head Life	: 400 million dots/needle
Buffer	: 512 KB
Compliance	: CE, RoHS Compliant, Safety : BIS approved
MTBF	: 10, 000 Hours

* Specifications are subject to change without prior notice

Lipi Data Systems Ltd

1, Mittal Chambers, Nariman Point, Mumbai 400 021, India

T: +91 22 2288 2960

E: contact@lipi.in W: www.lipi.in

An ISO 9001:2015, ISO 14001:2015 & ISO 45001:2018 certified company.

